

DT 250 / DT 252

Studio Headphones



DT 250



DT 252

FEATURES

- Closed headphone
- Excellent ambient noise attenuation
- Neodymium magnet system for perfect reproduction
- Soft, circumaural ear pads
- Single-sided plug-in type connecting cable
- DT 252 as single-sided version

APPLICATIONS

The DT 250 is a lightweight, closed dynamic headphone, which was specially designed for studio applications. It is featuring an efficient neodymium magnet system, a very high reproduction precision and a balanced sound. The wide transmission range between 10 - 30,000 Hz is another important feature.

The DT 250 comes with 80 Ω or 250 Ω systems.

The soft circumaural earcups offer a high wearing comfort and excellent ambient noise insulation. The padded headband is fully adjustable and can be adapted to each head size. The connecting cables to the earcups run safely in the headband. The main connecting cable is single-sided, plug-in type with a golden combi 1/4"/mini jack plug. All parts are easy to replace. The DT 252 is the single-sided version of the DT 250. This headphone is recommended for all broadcasting and theatre applications where the ambient contact is essential.

VERSIONS

- DT 250 Studio headphone, 80 Ω -system, with WK 250.07 coiled connecting cable with gold-plated mini stereo jack plug (3.5 mm) and 1/4" adapter (6.35 mm) . . . Order # 442.844
- DT 250 same as above, but 250 Ω system Order # 443.530
- DT 252 same as above, but single-sided version, 80 Ω , with WK 250.07 coiled cable Order # 445.177

OPTIONAL ACCESSORIES

- K 190.00 Bare-ended cable Order # 431.575

TECHNICAL SPECIFICATIONS

Transducer type	Dynamic
Operating principle	Closed
Transmission range	10 - 30,000 Hz
Nominal impedance	80 Ω
Nominal sound pressure level at 1 kHz	100 dB SPL at 1 mW = 0.28 V to 80 Ω
T.H.D.	< 1%
Nominal power rating	100 mW = 118 dB = 2.8 V to 80 Ω
Sound coupling to the ear	Circumaural
Ambient noise insulation	approx. 16 dBA
Average pressure on ears	4.5 N
Weight without cable	240 g (DT 250)
Cable length	3 m

SPARE PARTS

- EDT 250 V Ear pads, velours, circumaural. Order # 942.704
- EDT 250 S Ear pads, soft PVC, circumaural. Order # 943.549
- WK 250.07 Coiled connecting cable with gold-plated mini stereo jack plug and 1/4" adapter (6.35 mm) Order # 442.070
- BN 59-59/A Headband pad Order # 503.886

Germany

beyerdynamic GmbH & Co. KG
Theresienstr. 8 · 74072 Heilbronn – Germany
Tel. +49 (0)7131 / 617-0 · Fax +49 (0)7131 / 617-224
info@beyerdynamic.de · www.beyerdynamic.de

United States

beyerdynamic Inc. USA
56 Central Ave. · Farmingdale, NY 11735
Tel. +1 (631) 293-3200 · Fax +1 (631) 293-3288
salesUSA@beyerdynamic.com · www.beyerdynamic.com

Great Britain

beyerdynamic U.K. Ltd.
17 Albert Drive · Burgess Hill RH15 9TN
Tel. +44 (0)1444 / 258258 · Fax +44 (0)1444 / 258444
sales@beyerdynamic.co.uk · www.beyerdynamic.co.uk

DT 250 / DT 252



WIRING DIAGRAM

